

Table of Contents

Alphanumeric Index	x
Section 1 CMOS EPROMS	
CMOS EPROM Selection Guide	1-3
ONE TIME PROGRAMMABLE EPROMS AND SURFACE MOUNT PACKAGING—INTRODUCTION	1-4
NMC27C16 16,384-Bit (2048 x 8) UV Erasable CMOS PROM	1-5
NMC27C32 32,768-Bit (4096 x 8) UV Erasable CMOS PROM	1-12
NMC27C32B 32,768-Bit (4k x 8) High Speed Version UV Erasable CMOS PROM	1-19
NMC27C64 65,536-Bit (8k x 8) UV Erasable CMOS PROM	1-28
NMC27C64N 65,536-Bit (8k x 8) One-Time Programmable CMOS PROM	1-37
NMC27C128B High Speed Version 131,072 (16k x 8) CMOS PROM	1-46
NMC27C128BN High Speed Version 131,072-Bit (16k x 8) One-Time Programmable CMOS PROM	1-56
NMC27C256 262,144-Bit (32k x 8) UV Erasable CMOS PROM	1-67
NMC27C256B High Speed Version 262,144-Bit (32k x 8) UV Erasable CMOS PROM ..	1-76
NMC27C256BN High Speed Version 262,144-Bit (32k x 8) One-Time Programmable CMOS PROM	1-86
NMC27C512A 524,288-Bit High Speed Version (64k x 8) UV Erasable CMOS PROM ..	1-97
NMC27C512AN 524,288-Bit (64k x 8) One-Time Programmable CMOS PROM	1-107
NMC27C010 1,048,576-Bit (128k x 8) UV Erasable CMOS PROM	1-116
NMC27C1024 1,048,576-Bit (64k x 16) UV Erasable CMOS PROM	1-127
Section 2 EEPROMS	
Electrically Erasable Programmable Memory Selection Guide	2-3
SERIAL ELECTRICALLY ERASABLE PROGRAMMABLE MEMORY	
NMC9306 256-Bit Serial Electrically Erasable Programmable Memory	2-4
NMC93C06/C46 256-Bit/1024-Bit Serial Electrically Erasable Programmable Memory ..	2-11
NMC93CS06/CS46 256-Bit/1024-Bit Serial Electrically Erasable Programmable Memory	2-19
NMC9307 256-Bit Serial Electrically Erasable Programmable Memory	2-30
NMC9313B 256-Bit Serial Electrically Erasable Programmable Memory	2-36
NMC9346 1024-Bit Serial Electrically Erasable Programmable Memory	2-41
NMC9314B 1024-Bit Serial Electrically Erasable Programmable Memory	2-48
NMC93C56/C66 2048-Bit/4096-Bit Serial Electrically Erasable Programmable Memory	2-53
NMC93CS56/CS66 2048-Bit/4096-Bit Serial Electrically Erasable Programmable Memory	2-61
NMC93CS06x3/CS46x3/CS56x3/CS66x3 Extended Voltage Serial EEPROM	2-72
NMC93C06x3/C46x3/C56x3/C66x3 Extended Voltage Serial EEPROM	2-83
APPLICATION SPECIFIC EEPROM	
NMC95C12 1024-Bit CMOS EEPROM with DIP Switches	2-91
APPLICATIONS NOTES	
AB-15 Protecting Data in Serial Electrically Erasable Programmable Memory	2-100
AB-18 Electronic Compass Calibration Made Easy with Electrically Erasable Programmable Memory	2-102
AB-22 Automatic Low Cost Thermostat	2-103
AN-338 Designing with the NMC9306	2-105
AN-423 NMC9346—An Amazing Device	2-111
AN-431 An Easy/Low Cost Serial Electrically Erasable Programmable Memory Interface	2-114
AN-433 Using the NMC9306 for Configuration and Production Information	2-117
AN-481 Common I/O Applications for the NMC9306 and NMC9346	2-120

Table of Contents (Continued)

Section 2 EEPROMS (Continued)

AN-482 Error Detection and Correction Techniques	2-123
AN-507 Using the NMC93CSXX Family of Electrically Erasable Programmable Memory	2-128
Reliability of National Semiconductor's Electrically Erasable Programmable Memory Products	2-142

Section 3 PROMS

Bipolar PROM Selection Guide	3-3
------------------------------------	-----

NON-REGISTERED BIPOLAR PROMS

PL77/87X288B (32 x 8) 256-Bit TTL Logic PROMs	3-6
DM54/74S188 (32 x 8) 256-Bit TTL PROM	3-10
DM54/74S288 (32 x 8) 256-Bit TTL PROM	3-14
DM54/74S287 (256 x 4) 1024-Bit TTL PROM	3-18
DM54/74S387 (256 x 4) 1024-Bit TTL PROM	3-22
DM54/74LS471 (256 x 8) 2048-Bit TTL PROM	3-26
DM54/74S472 (512 x 8) 4096-Bit TTL PROM	3-30
DM54/74S473 (512 x 8) 4096-Bit TTL PROM	3-34
DM54/74S474 (512 x 8) 4096-Bit TTL PROM	3-38
DM54/74S475 (512 x 8) 4096-Bit TTL PROM	3-42
DM54/74S570 (512 x 4) 2048-Bit TTL PROM	3-46
DM54/74S571 (512 x 4) 2048-Bit TTL PROM	3-50
DM54/74S572 (1024 x 4) 4096-Bit TTL PROM	3-54
DM54/74S573 (1024 x 4) 4096-Bit TTL PROM	3-58
DM77/87S180, DM77/87S280 (1024 x 8) 8192-Bit TTL PROMs	3-62
DM77/87S181, DM77/87S281 (1024 x 8) 8192-Bit TTL PROMs	3-66
DM77/87S184 (2048 x 4) 8192-Bit TTL PROM	3-70
DM77/87S185 (2048 x 4) 8192-Bit TTL PROM	3-74

REGISTERED BIPOLAR PROMS

DM77/87SR474 (512 x 8) 4k-Bit Registered TTL PROM	3-78
DM77/87SR476 (512 x 8) 4k-Bit Registered TTL PROM	3-82
DM77/87SR27 (512 x 8) 4k-Bit Registered TTL PROM	3-86
DM77/87SR181 (1024 x 8) 8k-Bit Registered TTL PROM	3-91

APPLICATIONS INFORMATION

Bipolar PROM Devices in Plastic Leaded Chip Carriers	3-95
Non-Registered PROM Programming Procedure	3-99
Registered PROM Programming Procedure	3-101
Standard Test Load	3-103
Switching Time Waveforms	3-103
Approved Programmers/Quality Enhancement	3-105

Section 4 ECL I/O STATIC RAMS

BiCMOS ECL I/O SRAM Selection Guide	4-3
---	-----

BiCMOS SRAMS (ECL I/O)

NM5100/NM100500 ECL I/O 256k BiCMOS SRAM 262,144 x 1-Bit	4-4
NM100504/NM5104 256k BiCMOS SRAM 64k x 4 Bit	4-11
NM100494 64k BiCMOS SRAM 16k x 4 Bit	4-18
NM10494 64k BiCMOS SRAM 16k x 4 Bit	4-25
NM100492/NM4492 2k x 9 Advanced Self-Timed SRAM	4-32
NM10E149 256 x 4-Bit ECL EPROM	4-45
NM100E149 256 x 4-Bit ECL EPROM	4-53

Table of Contents (Continued)

Section 4 ECL I/O STATIC RAMS (Continued)

APPLICATION NOTES

AN-565 Memory System Efficiency and How National Semiconductor's 256k x 1 BiCMOS SRAM Helps.....	4-62
AN-566 National Semiconductor's BiCMOS III Process Is Latch-Up Immune.....	4-64
AN-567 Hot Carrier and Gate Oxide Reliability Characterization of National Semiconductor's BiCMOS III Technology.....	4-67
AN-568 The Reliability of National Semiconductor's 256k x 1 BiCMOS SRAM (NM5100/NM100500).....	4-69
AN-569 256k x 1 BiCMOS ECL SRAM Memory Cell Characterization and Alpha Sensitivity Testing.....	4-72
AN-572 Understanding Advanced Self-Timed SRAMs.....	4-73
AN-573 Design Considerations for High Speed Architectures.....	4-80

Section 5 TTL I/O STATIC RAMS

TTL I/O—MOS SRAM Selection Guide.....	5-3
---------------------------------------	-----

BIPOLAR STATIC RAMS

DM54S189/DM74S189 64-Bit (16 x 4) TRI-STATE RAM.....	5-4
DM54S189A/DM74S189A High Speed 64-Bit TRI-STATE RAM.....	5-4
DM74S289 64-Bit (16 x 4) Open Collector RAM.....	5-11
93L415A 1024 x 1-Bit Static Random Access Memory.....	5-15
93L422A 256 x 4-Bit Static Random Access Memory.....	5-20
93L425A 1024 x 1-Bit Static Random Access Memory.....	5-26
93479 256 x 9-Bit Static Random Access Memory.....	5-32

MOS STATIC RAMS

MM54/74C89 65-Bit TRI-STATE Random Access Read/Write Memory.....	5-39
MM54/74C200 256-Bit TRI-STATE Random Access Read/Write Memory.....	5-44
MM54/74C910 256-Bit TRI-STATE Random Access Read/Write Memory.....	5-48
MM54/74C989 64-Bit (16 x 4) TRI-STATE Random Access Memory.....	5-53
NMC2147H 4096 x 1-Bit Static RAM.....	5-57
NMC2148H 1024 x 4-Bit Static RAM.....	5-62

EDGE TRIGGERED REGISTERS

DM75S68/68A/85S68/68A 16 x 4 Edge Triggered Registers.....	5-67
--	------

Section 6 Appendices/Physical Dimensions

START™ Surface Mount Tape-and-Reel Specification.....	6-3
Physical Dimensions.....	6-31
Bookshelf.....	
Distributors.....	