

Contents

Nº 281

Preface xxi

Section 1 Introduction

INTRODUCTION..... 1-1

Section 2 Operational Amplifier and Comparator Theory

OPERATIONAL AMPLIFIER AND COMPARATOR THEORY..... 2-1

Operational Amplifier Theory..... 2-1

Major Performance Characteristics..... 2-2

Gain and Frequency Response..... 2-2

Gain-Bandwidth Product..... 2-3

Influence of the Input Resistance..... 2-3

Influence of Input Offset Voltage..... 2-3

Input Offset Compensation..... 2-4

Input Offset Temperature Coefficient..... 2-4

Influence of Input Bias Current..... 2-4

Influence of Output Resistance..... 2-5

Input Common-Mode Range..... 2-5

Common-Mode Rejection Ratio (CMRR)..... 2-5

Influence of Voltage and Current Drift..... 2-5

Slew Rate..... 2-5

Noise..... 2-6

Phase Margin..... 2-6

Output Voltage Swing (V_{opp})..... 2-6

Feed-Forward Compensation..... 2-6

Basic Operational Amplifier Circuits..... 2-7

Noninverting Operational Amplifier..... 2-7

Inverting Amplifiers..... 2-8

DC Output Offsets..... 2-8

Voltage Follower..... 2-9

Summing Amplifier..... 2-9

Difference Amplifier..... 2-9

Differentiator..... 2-9

Integrator..... 2-10

Active Filters..... 2-10

Unity-Gain Active Filters..... 2-10

Low-Pass Active Filters..... 2-11

Band-Reject Active Filters..... 2-11

Bandpass Active Filters..... 2-12

Choosing the Right Operational Amplifier..... 2-13

General Purpose Operational Amplifiers—Bipolar..... 2-13

BIFET Operational Amplifiers..... 2-14

LinCMOS Operational Amplifiers..... 2-14

Ultrastable Offsets..... 2-14

Wide Bandwidths..... 2-14

Advantages of LinCMOS Operational Amplifiers..... 2-15

Comparators..... 2-15

Comparator Parameters..... 2-16

Source Impedance..... 2-16

Differential Voltage Gain..... 2-16

Output Characteristics..... 2-16

| | |
|-----------------------------|------|
| Standard Comparators | 2-18 |
| Use of Hysteresis | 2-18 |
| Application Precaution..... | 2-18 |

Section 3 Operational Amplifier and Comparator Applications

| | |
|--|------|
| OPERATIONAL AMPLIFIER AND COMPARATOR APPLICATIONS..... | 3-1 |
| Operational Amplifier Applications | 3-1 |
| General Applications..... | 3-1 |
| Optical Sensor to TTL Interface Circuit | 3-1 |
| Bridge-Balance Indicator..... | 3-1 |
| High-Input-Impedance Differential Amplifier..... | 3-2 |
| Low Voltage Shunt Limiter | 3-3 |
| Schmitt Triggers | 3-3 |
| PTC Thermistor Automotive Temperature Indicator..... | 3-5 |
| Accurate 10-Volt Reference | 3-5 |
| Precision Large-Signal Voltage Buffer Using an OP-07 | 3-6 |
| Active Filter Applications | 3-6 |
| Active Filter Introduction | 3-6 |
| Active Band-Pass Filter | 3-7 |
| High- and Low-Pass Active Filters | 3-9 |
| Multiple-Feedback Band-Pass Filters | 3-9 |
| Twin-T Notch Filter..... | 3-10 |
| Audio Op Amp Applications..... | 3-11 |
| Mike Preamp with Tone Control | 3-11 |
| TL080 IC Preamplifier | 3-11 |
| Audio Distribution Amplifier | 3-13 |
| Audio Power Amplifier | 3-14 |
| Oscillators and Generators | 3-15 |
| Audio Oscillator Circuit Description | 3-15 |
| The Basic Multivibrator | 3-16 |
| LinCMOS Op Amp Applications..... | 3-17 |
| Microphone Preamplifier..... | 3-17 |
| Positive Peak Detector | 3-17 |
| Instrumentation Meter Driver | 3-18 |
| A Stable Two-Volt Logic Array Power Supply..... | 3-19 |
| TLC271 Twin-T Notch Filter | 3-20 |
| Single Supply Function Generator..... | 3-20 |
| Comparator Applications..... | 3-21 |
| Window Comparator | 3-21 |
| Comparator Interface Circuits..... | 3-21 |
| LM393 Zero-Crossing Detector | 3-23 |

Section 4 Video Amplifiers

| | |
|---|-----|
| VIDEO AMPLIFIERS | 4-1 |
| Video Amplifier Theory..... | 4-1 |
| Voltage Gain..... | 4-1 |
| Common-Mode Output Voltage | 4-1 |
| Output Offset Voltage | 4-2 |
| Wiring Precautions | 4-2 |
| Oscilloscope/Counter Preamplifier | 4-2 |
| NE592 Filter Applications..... | 4-3 |

| | |
|------------------------------------|-----|
| MC1445 Balanced Modulator | 4-3 |
| MC1445 Frequency Shift Keyer | 4-3 |

Section 5 Voltage Regulators

| | |
|---|------|
| VOLTAGE REGULATORS | 5-1 |
| Basic Regulator Theory | 5-1 |
| Voltage Regulator Components | 5-1 |
| Reference Elements | 5-1 |
| Sampling Element | 5-1 |
| Error Amplifier | 5-1 |
| Control Element | 5-1 |
| Regulator Classifications | 5-2 |
| Series Regulator | 5-2 |
| Shunt Regulator | 5-2 |
| Switching Regulator | 5-2 |
| Major Error Contributors | 5-3 |
| Regulator Reference Techniques | 5-3 |
| Zener Diode Reference | 5-3 |
| Constant-Current Zener Reference | 5-3 |
| Band-Gap Reference | 5-4 |
| Sampling Element | 5-5 |
| Error Amplifier Performance | 5-5 |
| Offset Voltage | 5-5 |
| Offset Change with Temperature | 5-5 |
| Supply Voltage Variations | 5-6 |
| Regulator Design Considerations | 5-6 |
| Positive Versus Negative Regulators | 5-6 |
| Fixed Versus Adjustable Regulators | 5-7 |
| Dual-Tracking Regulators | 5-7 |
| Series Regulators | 5-7 |
| Floating Regulator | 5-8 |
| Shunt Regulator | 5-9 |
| Switching Regulators | 5-9 |
| Fixed-On-Time, Variable Frequency | 5-10 |
| Fixed-Off-Time, Variable Frequency | 5-11 |
| Fixed-Frequency, Variable Duty Cycle | 5-11 |
| Regulator Safe Operating Area | 5-12 |
| Regulator SOA Considerations | 5-12 |
| Input Voltage | 5-12 |
| Load Current | 5-12 |
| Power Dissipation | 5-12 |
| Output Voltage of an Adjustable-Voltage Regulator | 5-12 |
| External Pass Transistor | 5-12 |
| Safe Operating Protection Circuits | 5-13 |
| Reverse Bias Protection | 5-13 |
| Current Limiting Techniques | 5-13 |
| Series Resistor | 5-13 |
| Constant-Current Limiting | 5-14 |
| Fold-Back Current Limiting | 5-14 |
| Three Thermal Regulators | 5-15 |
| Stabilization | 5-15 |
| Fixed Dual Regulators | 5-16 |
| Series Adjustable Regulators | 5-16 |

| | |
|---|------|
| Thermal Considerations | 5-17 |
| Layout Guidelines | 5-17 |
| Layout Design Factors | 5-17 |
| Input Ground Loop | 5-17 |
| Output Ground Loop | 5-17 |
| Remote Voltage Sense | 5-17 |
| Thermal Profile Concerns | 5-18 |
| Input Supply Design | 5-18 |
| Transformer/Rectifier Configuration | 5-18 |
| Capacitor Input Filter Design | 5-19 |
| Voltage Regulator Terms and Definitions | 5-21 |

Section 6 Switching Power Supply Design

| | |
|--|------|
| SWITCHING POWER SUPPLY DESIGN..... | 6-1 |
| Basic Operation of Switching Regulators | 6-1 |
| Advantages of a Switching Regulator | 6-2 |
| Disadvantages of a Switching Regulator | 6-2 |
| Basic Switching Regulator Architecture | 6-2 |
| The Step-Down Regulator | 6-2 |
| The Step-Up Regulator | 6-2 |
| The Inverting Regulator..... | 6-3 |
| Forward Converters..... | 6-3 |
| Push-Pull Converter..... | 6-3 |
| Half Bridge Converter | 6-3 |
| Full Bridge Converter..... | 6-4 |
| TL593 Floppy Disk Power Supply..... | 6-4 |
| Transformer Construction | 6-5 |
| TL594 12-Volt to 5-Volt Step-Down Regulator | 6-5 |
| The TL594 Control Circuit..... | 6-7 |
| Reference Regulator | 6-7 |
| Oscillator | 6-7 |
| Dead Time and PWM Comparators | 6-8 |
| Error Amplifiers..... | 6-9 |
| Output Logic Control | 6-9 |
| The Output Driver Stages..... | 6-9 |
| Soft-Start | 6-9 |
| Over-Voltage Protection | 6-9 |
| Designing a Power Supply (5 Volt/10 Amp Output)..... | 6-10 |
| Design Objective..... | 6-10 |
| Input Power Source | 6-10 |
| Control Circuits..... | 6-10 |
| Oscillator | 6-10 |
| Error Amplifier..... | 6-10 |
| Current Limit Amplifier..... | 6-10 |
| Soft-Start and Dead Time | 6-12 |
| Inductor Calculations | 6-12 |
| Output Capacitance Calculations | 6-12 |
| Transistor Power Switch Calculations..... | 6-13 |
| TL497A Switching Voltage Regulator | 6-13 |
| Step-Down Switching Regulator..... | 6-14 |
| Step-Up Switching Regulator..... | 6-14 |
| Inverting Configuration | 6-14 |
| Design Considerations | 6-17 |

| | |
|--|------|
| A Step-Down Switching Regulator Design Exercise with TL497A | 6-18 |
| Design and Operation of an Inverting Regulator Configuration | 6-19 |
| Adjustable Shunt Regulator TL430-TL431 | 6-21 |
| Shunt Regulator Applications (Crowbar) | 6-23 |
| Controlling V_o of a Fixed Output Voltage Regulator | 6-23 |
| Current Limiter | 6-23 |
| Voltmeter Scaler | 6-24 |
| Voltage-Regulated, Current-Limited Battery Charger for Lead-Acid Batteries | 6-24 |
| Battery Charger Design | 6-24 |
| Rectifier Section | 6-25 |
| Voltage Regulator Section | 6-25 |
| Current Limiter Section | 6-26 |
| Series Pass Element | 6-26 |
| Design Calculations | 6-26 |
| Power Dissipation and Heat Sinking | 6-27 |
| Voltage Supply Supervisor Devices | 6-27 |
| General Operation | 6-28 |
| TL7700 Series Supervisor Chips | 6-28 |
| Operation During a Voltage Drop | 6-29 |
| TL7700 Series Application | 6-30 |
| uA723 Precision Voltage Regulator | 6-31 |
| Typical Applications | 6-32 |
| General Purpose Power Supply | 6-34 |
| 8-Amp Regulated Power Supply for Operating Mobile Equipment | 6-35 |
| ± 15 Volts at 1.0 Amp Regulated Power Supplies | 6-36 |
| Positive Supply | 6-36 |
| Negative Supply | 6-36 |
| Overvoltage Sensing Circuits | 6-38 |
| The Crowbar Technique | 6-38 |
| Activation Indication Output | 6-38 |
| Remote Activation Input | 6-38 |

Section 7 Integrated Circuit Timers

| | |
|---|-----|
| INTEGRATED CIRCUIT TIMERS | 7-1 |
| RC Time-Base Generator | 7-1 |
| A Basic Delay Timer | 7-1 |
| NE/SE555 Timers | 7-2 |
| Definition of Block Diagram Functions | 7-2 |
| Threshold Comparator | 7-2 |
| Trigger Comparator | 7-2 |
| RS Flip-Flop | 7-2 |
| Discharge Transistor | 7-2 |
| Output Stage | 7-2 |
| 555 Basic Operating Modes | 7-3 |
| Monostable Mode | 7-4 |
| Astable Mode | 7-5 |
| Accuracy | 7-5 |
| TLC555 Timer | 7-5 |
| TLC555 Astable Timing Equations | 7-6 |
| TLC556/NE556 Dual Unit | 7-6 |
| uA2240 Programmable Timer/Counter | 7-7 |
| Definition of uA2240 Functions | 7-7 |
| Voltage Regulator (V_{reg}) | 7-7 |

| | |
|--|------|
| Control Logic | 7-8 |
| Time Base Oscillator | 7-8 |
| RC Input | 7-8 |
| Modulation and Sync Input | 7-8 |
| Threshold Comparators | 7-9 |
| Oscillator Flip-Flop | 7-9 |
| Binary Counter | 7-9 |
| uA2240 Basic Operating Modes | 7-9 |
| Monostable Operating Mode | 7-9 |
| Astable Operating Mode | 7-10 |
| Accuracy | 7-10 |
| General Design Considerations | 7-10 |
| Missing Pulse Detector | 7-11 |
| NE555 One-Shot Timer | 7-13 |
| Oscilloscope Calibrator | 7-13 |
| Darkroom Enlarger Timer | 7-14 |
| Touch Switch | 7-15 |
| Basic Square Wave Oscillator | 7-15 |
| Linear Ramp Generator | 7-15 |
| Fixed-Frequency Variable-Duty-Cycle Oscillator | 7-17 |
| Alternating LED Flasher | 7-17 |
| Positive-Triggered Monostable | 7-18 |
| Voltage Controlled Oscillator | 7-18 |
| Capacitance-to-Voltage Meter | 7-20 |
| TLC555 PWM Motor Controller | 7-22 |
| Telephone Controlled Night Light | 7-23 |
| Programmable Voltage Controlled Timer | 7-23 |
| Frequency Synthesizer | 7-25 |
| Cascaded Times for Long Time Delays | 7-25 |
| uA2240 Operation with External Clock | 7-26 |
| uA2240 Staircase Generator | 7-28 |

Section 8 Display Drivers

| | |
|--|------|
| DISPLAY DRIVERS | 8-1 |
| Introduction to Display Driver Technology | 8-1 |
| LED Display Drivers | 8-3 |
| SN75491 and SN75491A Quad LED Segment Drivers | 8-3 |
| SN75492 and SN75492A Hex LED Digit Drivers | 8-3 |
| SN75494 Hex LED Digit Driver | 8-4 |
| SN75497 7-Channel and SN75498 9-Channel LED Drivers | 8-4 |
| Driving LED Displays | 8-4 |
| Other Applications | 8-7 |
| DC Plasma Display Drivers | 8-9 |
| SN75480 DC Plasma Driver | 8-9 |
| SN75480 Application | 8-11 |
| SN75581 Gas Discharge Source Driver | 8-11 |
| SN75581 Application | 8-11 |
| SN75584A High-Voltage 7-Segment Latch/Decoder/Cathode Driver | 8-11 |
| SN75584A Application | 8-15 |
| AC Plasma Display Drivers | 8-16 |
| AC Plasma Display Technology | 8-16 |
| Construction | 8-16 |

| | |
|--|------|
| The Functional Cell | 8-17 |
| Control Circuitry Implementation with the SN75500A and SN75501C..... | 8-17 |
| The Functional Waveforms | 8-19 |
| SN75500A AC Plasma Display Axis Driver..... | 8-21 |
| SN75501C AC Plasma Display Axis Driver..... | 8-24 |
| Functional Adaptation of the SN75500A and SN75501C | 8-24 |
| Strobing and Sustaining | 8-24 |
| Floating Driver Considerations | 8-25 |
| Data Coupling Considerations | 8-27 |
| Vacuum Fluorescent Displayer | 8-29 |
| Introduction | 8-29 |
| The VFD Panel | 8-29 |
| Construction | 8-29 |
| Panel Performance | 8-30 |
| VFD Timing Requirements | 8-31 |
| Drive Electronics | 8-31 |
| The UCN4810A 10-Bit VFD Driver..... | 8-31 |
| The TL4810A 10-Bit VFD Driver | 8-32 |
| The SN75512A 12-Bit VFD Driver | 8-33 |
| The SN75513A 12-Bit VFD Driver | 8-33 |
| The SN75514 High Voltage 12-Bit VFD Driver..... | 8-33 |
| The SN75518 32-Bit VFD Driver..... | 8-34 |
| The SN75501C as a 32-Bit High-Voltage VFD Driver..... | 8-35 |
| VFD Driver Applications | 8-35 |
| Driving a Vacuum Fluorescent Character Display..... | 8-35 |
| Driving a Dot Matrix Display | 8-36 |
| AC Thin Film Electroluminescent Display Drivers..... | 8-42 |
| AC TFEL Display Technology | 8-42 |
| Factors Affecting TFEL Display Brightness | 8-42 |
| AC TFEL Pixel Equivalent Circuit | 8-43 |
| Drivers for AC TFEL Panels..... | 8-43 |
| SN75551 and SN75552 Electroluminescent Row Drivers | 8-44 |
| SN75553 and SN75554 Electroluminescent Column Drivers..... | 8-44 |
| Driving AC TFEL Panels | 8-44 |
| Practical Refresh Drive Scheme | 8-44 |
| Theory of Operation | 8-44 |
| Interconnecting the Drivers to the Panel | 8-47 |
| Row Driver Operation | 8-47 |
| Column Driver Operation | 8-47 |
| Row and Column Driver Requirements | 8-47 |
| Row Driver Voltage Supply | 8-48 |
| Composite Row Driver..... | 8-49 |
| Specifying Driver Requirements..... | 8-50 |

Section 9 Data Transmission

| | |
|--|-----|
| DATA TRANSMISSION..... | 9-1 |
| General Purpose Data Transmission..... | 9-1 |
| General Requirements | 9-1 |
| Types of Transmission Lines | 9-1 |
| Single Wire and Ground Plane | 9-1 |
| Two-Wire Interconnect..... | 9-2 |
| Twisted Pair | 9-2 |
| Coaxial Lines | 9-4 |

| | |
|--|------|
| Line Drivers | 9-4 |
| Basic Driver Modes | 9-5 |
| Types of Transmission | 9-5 |
| Single-Ended Transmission | 9-5 |
| Single-Ended Application for High-Speed Bus Communication | 9-8 |
| Differential Line Drivers and Receivers | 9-11 |
| Terminating Differential Data Transmission | 9-12 |
| Current-Mode Drivers in Differential Data Line Transmission | 9-13 |
| Receiver Performance | 9-15 |
| Input Sensitivity | 9-15 |
| Common-Mode Voltage Range | 9-15 |
| Input Termination Resistors | 9-16 |
| Reference Voltage | 9-16 |
| Input Limitations | 9-17 |
| SN55/75107A Series Applications | 9-17 |
| Connection of Unused Inputs and Outputs | 9-17 |
| One-Channel Balanced Transmission System | 9-17 |
| Differential Party-Line Systems | 9-17 |
| Repeaters for Long Lines | 9-18 |
| Standard Voltage-Mode Differential Drivers and Receivers | 9-19 |
| EIA Standard RS-232-C Circuits and Applications | 9-22 |
| Typical Drivers for EIA RS-232-C Applications | 9-22 |
| SN75150 Dual Data Line Driver | 9-22 |
| SN75156/ μ A9636 Dual Line Driver | 9-22 |
| SN75188/MC1488 Quad Line Driver | 9-24 |
| Typical Receivers for EIA RS-232-C Applications | 9-24 |
| SN75152 Dual Data Line Receiver | 9-24 |
| SN75154 Quad Data Line Receiver | 9-28 |
| SN75189, SN75189A, MC1489 and MC1489A Quad Line Receivers | 9-29 |
| RS-232-C Applications | 9-32 |
| Interface Using SN75150 and SN75154 | 9-32 |
| Typical Interface Using SN75188 and SN75189A | 9-33 |
| EIA Standard RS-423-A Circuits and Applications | 9-33 |
| RS-423-A Standard | 9-33 |
| RS-423-A Devices | 9-33 |
| RS-423-A Drivers | 9-33 |
| RS-423-A Receivers | 9-36 |
| Basic RS-423-A Application | 9-36 |
| EIA Standard RS-422-A and RS-485 Circuits and Applications | 9-37 |
| RS-422-A Standard | 9-37 |
| RS-422-A Applications | 9-40 |
| Typical Application | 9-40 |
| Short-Line Application | 9-40 |
| EIA RS-485 Standard | 9-40 |
| Unit Load Circuit | 9-41 |
| Drivers and Receivers | 9-41 |
| Driver Details | 9-42 |
| Driver Speed Characteristics | 9-43 |
| Receiver Details | 9-44 |
| Transceivers | 9-45 |
| SN75176B, SN75177B, SN75178B and SN75179B Transceiver Features | 9-45 |
| Basic Transceiver Application | 9-45 |
| Long-Line Application | 9-46 |
| SN75179B Application | 9-46 |
| IEEE 488-1978 Transmission Systems | 9-46 |

| | |
|--|------|
| The IEEE-488 Standard..... | 9-46 |
| General Information | 9-46 |
| Connectors..... | 9-48 |
| Cable..... | 9-49 |
| Logic Convention | 9-49 |
| Functions | 9-49 |
| Messages or Commands..... | 9-50 |
| Bus Interface Devices..... | 9-51 |
| Electrical Specifications | 9-52 |
| Driver Requirements..... | 9-52 |
| Driver Specifications | 9-52 |
| Receiver Specifications..... | 9-52 |
| Composite Load Requirements..... | 9-52 |
| Device DC Load Line Boundaries..... | 9-52 |
| Device AC Load Line Limit | 9-52 |
| Device Capacitive Load Limit..... | 9-52 |
| Timing Values | 9-53 |
| Data Rates..... | 9-53 |
| Interfacing to the IEEE Standard 488 Bus..... | 9-53 |
| SN75160A Octal GPIB Transceiver | 9-53 |
| SN75163A Octal GPIB Transceiver | 9-54 |
| SN75161A and SN75162A Octal GPIB Transceiver..... | 9-54 |
| MC3446 Quad Bus Transceiver..... | 9-56 |
| Typical Applications | 9-56 |
| A Typical IEEE-488 System Application | 9-57 |
| IBM System 360/370 Interfacing Circuits..... | 9-58 |
| Driver and Receiver Requirements..... | 9-59 |
| Driver Requirements..... | 9-59 |
| Receiver Requirements | 9-62 |
| General Physical and Electrical Requirements..... | 9-62 |
| Line Terminations | 9-62 |
| Voltage Levels | 9-62 |
| Cable | 9-62 |
| Ground Shift and Noise | 9-62 |
| Fault Conditions | 9-62 |
| Electrical Characteristics for Select Out Interface..... | 9-63 |
| Receiver Requirements | 9-63 |
| Driver Requirements..... | 9-63 |
| IBM System/360 and System/370 Data Line Drivers | 9-63 |
| SN75123 Dual Line Driver | 9-63 |
| SN75126 Quadruple Line Driver | 9-64 |
| SN75130 Quadruple Line Driver | 9-65 |
| IBM System/360 and System/370 Data Line Receivers | 9-65 |
| SN75124 Triple Line Receiver..... | 9-65 |
| SN75125 and SN75127 Seven-Channel Line Receivers..... | 9-66 |
| SN75128 and SN75129 Octal Line Receivers..... | 9-67 |
| IBM System 370 Application..... | 9-67 |
| Drivers | 9-67 |
| Cable | 9-68 |
| Receivers | 9-68 |

Section 10 Peripheral Drivers

| | |
|--|------|
| PERIPHERAL DRIVERS | 10-1 |
| Device Considerations and Product Descriptions | 10-1 |

| | |
|---|-------|
| Basic Configurations | 10-1 |
| Typical Requirements | 10-1 |
| Power | 10-1 |
| Voltage | 10-2 |
| Current | 10-2 |
| Speed | 10-2 |
| Logic | 10-2 |
| Peripheral Driver Devices | 10-2 |
| SN75431, '461 and '471 Series | 10-4 |
| SN75446 and SN75476 Series | 10-4 |
| SN75436, SN75437A and SN75438 | 10-5 |
| SN75435 Quad Driver | 10-6 |
| SN75440 Quad Peripheral Driver | 10-7 |
| SN75603, SN75604, and SN75605 | 10-7 |
| SN75372 Dual and SN75374 Quad Power FET Drivers | 10-8 |
| DS3680 Quad Telephone Relay Driver | 10-9 |
| SN75064/U LN2064 Series Quad Peripheral Drivers | 10-10 |
| SN75068/U LN2068 and SN75069/U LN2069 Quad Darlington Switches | 10-12 |
| SN75074/U LN2074 and SN75075/U LN2075 Quad Darlington Sink or Source Drivers | 10-12 |
| SN75465 and U LN2001A Series Seven Channel Darlington Transistor Arrays | 10-12 |
| UDN2841 and UDN2845 Quad High Current Darlington Drivers | 10-13 |
| Peripheral Driver Applications | 10-14 |
| Peripheral Driver-Opto Applications | 10-14 |
| Driving Tungsten Filament, or Equivalent, Incandescent Lamps | 10-14 |
| Driving Remotely Located LED Devices | 10-17 |
| Relay and Solenoid Driver Applications | 10-17 |
| Printer Hammer Driver Application | 10-18 |
| Driving a Reversible Solenoid | 10-18 |
| Opto Isolated and Time Controlled Reversible Solenoid Drive | 10-18 |
| Power Solenoid Drive | 10-21 |
| Intelligent Switches | 10-21 |
| Automotive Lights On Warning | 10-21 |
| Driving Motors | 10-21 |
| "H" or Bridge Drive | 10-21 |
| "H" Motor Drive for Negative Supplies | 10-22 |
| Speed Controlled, Reversible DC Motor Drive with the SN75603 and SN75604 | 10-22 |
| Driving Power FETs for DC Motor Control | 10-23 |
| Stepper Motor Drive | 10-23 |
| Driving Data Transmission Lines | 10-26 |

Section 11

Data Acquisition Systems

| | |
|-------------------------------------|------|
| DATA ACQUISITION SYSTEMS | 11-1 |
| Typical Systems | 11-1 |
| Microprocessor-Controlled DAS | 11-2 |
| Basic Uses of a DAS | 11-2 |
| Data Logging | 11-2 |
| Signal Analysis | 11-2 |
| Process Control | 11-2 |
| Basic Sampling Concepts | 11-2 |
| Types of Signals | 11-3 |
| DC Signals | 11-3 |
| Dynamic Signals | 11-3 |
| Deterministic Signals | 11-3 |

| | |
|--|-------|
| Random Signals..... | 11-4 |
| Frequently Used Terms and Concepts..... | 11-5 |
| The Sampling Theorem..... | 11-5 |
| Aliasing..... | 11-6 |
| The Nyquist Criterion..... | 11-6 |
| Aliasing Filter..... | 11-6 |
| Quantization..... | 11-7 |
| Binary Codes..... | 11-7 |
| Straight and Offset Binary Codes..... | 11-7 |
| One's and Two's Complement Codes..... | 11-8 |
| Absolute-Value-Plus-Sign Code..... | 11-8 |
| Gray Code..... | 11-8 |
| BCD Code..... | 11-9 |
| Signal Recovery..... | 11-9 |
| A Data Requisition Example..... | 11-10 |
| Summary of Design Considerations..... | 11-12 |
| System Parameters..... | 11-12 |
| Understanding Major System Parameters..... | 11-12 |
| Methods of A/D Conversion..... | 11-14 |
| Key Selection Criteria for A/D Converters..... | 11-14 |
| Number of Bits..... | 11-14 |
| Conversion Speed..... | 11-14 |
| Conversion Accuracy..... | 11-14 |
| Conversion Techniques..... | 11-15 |
| Single-Slope A/D Converter..... | 11-15 |
| Dual-Slope A/D Converter..... | 11-16 |
| Successive-Approximation Converters..... | 11-17 |
| Binary Bit Weighing..... | 11-19 |
| Creating a Digital Number..... | 11-19 |
| Flash A/D Converters..... | 11-20 |
| Device Types..... | 11-21 |
| ADC0803 and ADC0805 8-Bit Successive-Approximation A/D Converters with Differential Inputs..... | 11-21 |
| Description..... | 11-21 |
| Principles of Operation..... | 11-21 |
| ADC0808, ADC0809 CMOS Analog-to-Digital Converters with 8-Channel Multiplexers..... | 11-23 |
| Description..... | 11-23 |
| Multiplexer..... | 11-24 |
| Converter..... | 11-25 |
| ADC0831, ADC0832, ADC0834, ADC0838 2-, 4-, 8-Channel A/D Peripherals with Serial Control and Multiplexer Options..... | 11-26 |
| Description..... | 11-26 |
| Principles of Operation..... | 11-33 |
| TL500C thru TL503C Analog-to-Digital Converter Building Blocks TL500C/TL501C... TL502C/TL503C..... | 11-34 |
| General Overall Description..... | 11-35 |
| Description of TL500C and TL501C Analog Processors..... | 11-37 |
| Description of TL502C/503C Digital Processors..... | 11-37 |
| Principles of Operation..... | 11-39 |
| Auto-Zero Phase..... | 11-41 |
| Integrate-Input Phase..... | 11-41 |
| Integrate-Reference Phase..... | 11-41 |
| Capacitor Selection Guidelines..... | 11-41 |
| Bypassing and Stray Coupling..... | 11-41 |

| | |
|--|-------|
| TL505C Analog-to-Digital Converter..... | 11-41 |
| Description | 11-41 |
| Definition of Terms | 11-42 |
| Principles of Operation..... | 11-42 |
| TL5071, TL507C Analog-to-Digital Converter..... | 11-44 |
| Description | 11-44 |
| Definition of Terms | 11-44 |
| Principles of Operation..... | 11-44 |
| TLC532, TLC533 LinCMOS 8-Bit Analog-to-Digital Peripherals with 5 Analog and 6 Multipurpose Inputs | 11-47 |
| Description | 11-47 |
| Principles of Operation..... | 11-48 |
| TLC540, TLC541 8-Bit Analog-to-Digital Peripherals with Serial Control and 11 Inputs | 11-51 |
| Description | 11-51 |
| Principles of Operation..... | 11-51 |
| TLC548, TLC549, LinCMOS 8-Bit Analog-to-Digital Converters with Serial Control ... | 11-53 |
| Description | 11-53 |
| Principles of Operation..... | 11-54 |
| TL0808, TL0809 Low-Power CMOS Analog-to-Digital Converter with 8-Channel Multiplexers | 11-55 |
| Description | 11-55 |
| Principles of Operation..... | 11-56 |
| Multiplexer | 11-57 |
| Converter..... | 11-57 |
| A/D Converter Applications | 11-58 |
| Interface for ADC0803, ADC0804, and ADC0805 Converters to Zilog Z80A and Z80 Microprocessors..... | 11-58 |
| Circuitry | 11-59 |
| Timing Diagram | 11-59 |
| Software | 11-59 |
| Interface for ADC0803, ADC0804, and ADC0805 Converters to the Rockwell 6502 Microprocessor | 11-61 |
| Interface for ADC0808, ADC0809, TL0808, TL0809, TL520, TL521, and TL522 Converters to Zilog Z80A and Z80 Microprocessor | 11-62 |
| Timing Diagram | 11-63 |
| Software | 11-63 |
| Interface for ADC0808 and ADC0809 Converters to the Rockwell 6502 Microprocessor | 11-66 |
| Interface for ADC0808, ADC0809, TL0808, TL0809, TL520, TL521, and TL522 Converters to the Motorola 6800 Microprocessors..... | 11-68 |
| Timing Diagram | 11-68 |
| Software | 11-68 |
| Interface for ADC0831, ADC0832, ADC0834, and ADC0838 Converters to Zilog Z80A and Z80 Microprocessors..... | 11-71 |
| Circuitry—ADC0832, ADC0834, and ADC0838..... | 11-71 |
| Timing Diagram—ADC0838 Device | 11-71 |
| Software—ADC0832, ADC0834, and ADC0838 Devices..... | 11-72 |
| Circuitry—ADC0831 Device | 11-75 |
| Timing Diagram—ADC0831 Device | 11-75 |
| Software—ADC0831 Device | 11-75 |
| Interface for ADC0831, ADC0832, and ADC0838 Converters to the Rockwell 6502 Microprocessor | 11-77 |
| Interface for ADC0831, ADC0832, ADC0834, and ADC0838 Converters to the Motorola 6805 Microprocessor | 11-80 |

| | |
|---|--------|
| Circuitry—ADC0832, ADC0834, and ADC0838 Devices | 11-80 |
| Timing Diagrams—ADC0838 Device | 11-80 |
| Software—ADC0832, ADC0834, and ADC0838 Devices | 11-80 |
| Circuitry—ADC0831 Device | 11-83 |
| Timing Diagram—ADC0831 Device | 11-83 |
| Software—ADC0831 Device | 11-83 |
| Interface for ADC0831, ADC0832, ADC0834, and ADC0838 Converters to Motorola | |
| 6800, 6802, 6809, and 6809E Microprocessors | 11-84 |
| Circuitry—ADC0832, ADC0834, and ADC0838 Devices | 11-85 |
| Timing Diagram—ADC0838 Device | 11-85 |
| Software—ADC0832, ADC0834, and ADC0838 Devices | 11-86 |
| Circuitry—ADC0831 Device | 11-89 |
| Timing Diagram—ADC0831 Device | 11-89 |
| Software—ADC0831 Device | 11-89 |
| Interface for ADC0831, ADC0832, ADC0834, and ADC0838 Converters to Intel | |
| 8051 and 8502 Microprocessors | 11-91 |
| Circuitry—ADC0832, ADC0834, and ADC0838 Devices | 11-91 |
| Timing Diagram—ADC0838 Device | 11-91 |
| Software | 11-93 |
| Circuitry—ADC0831 Device | 11-95 |
| Timing Diagram—ADC0831 Device | 11-95 |
| Software—ADC0831 Device | 11-96 |
| Interface for ADC0831, ADC0832, ADC0834, and ADC0838 Converters to Intel | |
| 8048 and 8049 Microprocessors | 11-97 |
| Circuitry—ADC0838, ADC0834, and ADC0832 | 11-97 |
| Timing Diagram—ADC0838 Device | 11-97 |
| Software—ADC0838, ADC0834, and ADC0832 Devices | 11-97 |
| Circuitry—ADC0831 Device | 11-98 |
| Timing Diagram—ADC0831 Device | 11-98 |
| Software—ADC0831 Device | 11-98 |
| TL500, TL501, TL502, and TL503 Devices Application Examples | 11-100 |
| External Components Selection Guide | 11-100 |
| Printed Circuit Board Layout Notes | 11-101 |
| TL502 and TL503 Control Circuits | 11-101 |
| Logic Inputs and Outputs | 11-101 |
| Driving a Display Using the TL502 Device | 11-104 |
| Calculation of the Current-Limiting Resistor | 11-104 |
| Application of the TL503 BCD Outputs | 11-104 |
| Digital Panel Meter Using the TL501 and TL502 Devices | 11-105 |
| Digital Thermometer | 11-107 |
| Precision Panel Meter Application | 11-107 |
| TL505 A/D Converter Applications | 11-109 |
| Functional Description | 11-109 |
| External Component Selection Guide | 11-109 |
| Digital Panel Meter Using the TL505 and TL502 Devices | 11-110 |
| TL505 to TMS1000 Interface | 11-111 |
| TL507 A/D Converter Applications | 11-112 |
| TL507 Device Description | 11-112 |
| TL507 Device Inputs and Outputs | 11-113 |
| Single-Wire Power, Data, and Clock Cycle Transmitter | 11-115 |
| TL507 High Voltage Insulation Application and Signal Coupling | 11-116 |
| TL507 to TMS1000 Interface | 11-116 |
| TL507 to TMS1000C Interface | 11-117 |
| Summary | 11-118 |

| | |
|---|--------|
| Interface for TLC532A, TLC533A, TL530, and TL531 Devices to Zilog Z80A and Z80 Microprocessors | 11-118 |
| Input/Output Mapping | 11-120 |
| Timing Diagram | 11-120 |
| Software | 11-120 |
| Additional Comments | 11-121 |
| Interface for TLC532A, TLC533A, TL530, and TL531 Devices to Intel 8048 and 8049 and Intel 8051 and 8052 Microprocessors | 11-122 |
| Hardware—Interface 1 | 11-122 |
| Timing Diagram—Interface 1 | 11-122 |
| Software—Interface 1 | 11-122 |
| Hardware—Interface 2 | 11-126 |
| Timing Diagram—Interface 2 | 11-126 |
| Software—Interface 2 | 11-126 |
| Additional Comments | 11-129 |
| Interface for TLC532A, TLC533A, and TL530 Devices to the Rockwell 6502 Microprocessor | 11-129 |
| Principles of Operation | 11-129 |
| Interface for TLC532A, TLC533A, TL530, and TL531 Devices to the Motorola 6800, 6802, 6809, and 6809E Microprocessors | 11-131 |
| Input/Output Mapping | 11-131 |
| Timing Diagram | 11-132 |
| Software | 11-132 |
| Considerations for Different Microprocessors | 11-135 |
| Interface Selection | 11-136 |
| Additional Comments | 11-136 |
| Interface for the TLC540 Device to Zilog Z80A and Z80 Microprocessor | 11-137 |
| Interface 1 | 11-137 |
| Interface 2 | 11-139 |
| Interface for the TLC540 Device to the Rockwell 6502 Microprocessor Using the 6522 VIA | 11-140 |
| Principles of Operation | 11-140 |
| Interface for the TLC540 Device to the Rockwell Microprocessor Using TTL Gates ... | 11-142 |
| Principles of Operation | 11-142 |
| Interface for TLC540 and TLC541 Devices to the Motorola 6805 Microprocessor | 11-144 |
| Principles of Operation | 11-144 |
| Software Interface for TLC540 and TLC541 Devices to Intel 8051 and 8052 Microprocessors | 11-146 |
| Circuit—Interface 1 (ALE CLOCK) | 11-148 |
| Circuit—Interface 2 (CRYSTAL CLOCK) | 11-148 |
| Timing Diagrams | 11-148 |
| Software | 11-148 |
| Hardware | 11-151 |
| Timing Diagrams | 11-151 |
| Software | 11-151 |
| Software Interface for TLC540 and TLC541 Devices to Intel 8048 and 8049 Microprocessors | 11-151 |
| Hardware | 11-151 |
| Timing Diagram | 11-151 |
| Software | 11-151 |
| Interface for the TLC549 Device to the Zilog Z80A Microprocessor | 11-156 |
| Principles of Operation | 11-156 |
| Interface for the TLC549 Device to the Rockwell 6502 Microprocessor Using TTL Gates | 11-157 |
| Principles of Operation | 11-157 |

| | |
|---|--------|
| Interface for the TLC549 Device to the Rockwell 6502 Microprocessor Using the 6522 VIA | 11-158 |
| Principles of Operation..... | 11-158 |
| Interface for the TLC549 Device to the Motorola 6805 Microprocessor | 11-160 |
| Principles of Operation..... | 11-160 |
| Software Interface for the TLC549 Device to Intel 8048 and 8049 Microprocessors..... | 11-161 |
| Hardware | 11-161 |
| Timing Diagram | 11-161 |
| Software | 11-163 |
| Serial Port Interface for the TLC549 Device to Intel 8051 and 8052 Microprocessors ... | 11-163 |
| Hardware | 11-164 |
| Timing Diagram | 11-164 |
| Software | 11-164 |
| Software Interface for the TLC549 Device to Intel 8051 and 8052 Microprocessors..... | 11-166 |
| Hardware | 11-166 |
| Timing Diagram | 11-166 |
| Software | 11-167 |
| Interface for TLC1540 and TLC1541 Devices to the Zilog Z80A Microprocessor..... | 11-169 |
| Principles of Operation..... | 11-169 |
| Interface for TLC1540 and TLC1541 Devices to the Rockwell 6502 Microprocessor | 11-170 |
| Hardware | 11-170 |
| Timing Diagram | 11-170 |
| Software | 11-171 |
| Interface for TLC1540 and TLC1541 Devices to the Motorola 6802 Microprocessor | 11-172 |
| Principles of Operation..... | 11-173 |
| Software Interface for TLC1540 and TLC1541 Devices to the Motorola 6805 Microprocessor | 11-174 |
| Hardware | 11-174 |
| Software | 11-174 |
| Software Interface for TLC1540 and TLC1541 Devices to the Intel 8051 and 8052 Microprocessor | 11-176 |
| Hardware | 11-176 |
| Timing Diagram | 11-176 |
| Software | 11-176 |
| Hardware Interface for the TLC545 Device to the Zilog Z80A Microprocessor | 11-178 |
| Principles of Operation..... | 11-178 |
| Software Interface for the TLC545 Device to the Zilog Z80A Microprocessor | 11-179 |
| Principles of Operation..... | 11-179 |
| Software Interface for the TLC545 and TLC546 Devices to Intel 8051 and 8052 Microprocessors | 11-181 |
| Hardware | 11-181 |
| Timing Diagram | 11-181 |
| Software | 11-181 |
| Serial Port Interface for TLC545 and TLC546 Devices to Intel 8051 and 8052 Microprocessors | 11-185 |
| Hardware | 11-185 |
| Timing Diagram | 11-186 |
| Software | 11-187 |
| Interface for the TLC545 Device to the Rockwell 6502 Microprocessor Using TTL Gates..... | 11-190 |
| Principles of Operation..... | 11-190 |
| Interface for the TLC545 Device to the Rockwell 6502 Microprocessor Using the 6522 VIA | 11-191 |
| Principles of Operation..... | 11-191 |
| Interface for the TLC545 and TLC546 Devices to the Motorola 6805 Microprocessor .. | 11-193 |

| | |
|---|--------|
| Principles of Operation..... | 11-194 |
| Introduction to Data Acquisition for Digital Signal Processors..... | 11-195 |
| Interfacing the TLC32040 to the TMS320 Family of Digital Signal Processors..... | 11-196 |
| Description..... | 11-196 |
| Principles of Operation..... | 11-196 |
| Interfacing the TLC7524 to the TMS32010..... | 11-199 |
| Hardware..... | 11-199 |
| Principles of Operation..... | 11-200 |
| Interfacing the TLC0820 to the TMS32010..... | 11-201 |
| Hardware..... | 11-201 |
| Principles of Operation..... | 11-201 |
| Interfacing the TLC7524 to the TMS32020..... | 11-202 |
| Hardware..... | 11-202 |
| Principles of Operation..... | 11-202 |
| Interfacing the TLC0820 to the TMS32020..... | 11-205 |
| Hardware..... | 11-205 |
| Principles of Operation..... | 11-205 |
| Interfacing the TLC1540, TLC1541, TLC540, and TLC541 to the TMS32020 and TSMS320C25..... | 11-207 |
| Hardware..... | 11-207 |
| Software..... | 11-209 |
| Other Considerations..... | 11-209 |
| Interfacing the TLC548/9 to the TMS32020..... | 11-211 |
| Hardware..... | 11-211 |
| Principles of Operation..... | 11-211 |

Section 12 Special Functions

| | |
|--|-------|
| SPECIAL FUNCTIONS..... | 12-1 |
| The Hall Effect..... | 12-1 |
| The Hall Effect in Silicon..... | 12-1 |
| Hall-Effect Devices..... | 12-2 |
| Switching Devices..... | 12-2 |
| Latching Devices..... | 12-2 |
| Linear Hall Devices..... | 12-2 |
| Advantages of Hall-Effect Devices..... | 12-3 |
| Hall-Effect Device Selection..... | 12-3 |
| Hall-Effect Applications..... | 12-4 |
| TL3103 Linear Hall-Effect Device in Isolated Sensing Applications..... | 12-4 |
| Toroid Design..... | 12-5 |
| TL594 Isolated Feedback Power Supply..... | 12-5 |
| Tachometer and Direction of Rotation Circuit..... | 12-5 |
| Tachometer Operation..... | 12-7 |
| Direction of Rotation Circuit..... | 12-8 |
| LED V_{cc} Supply Control..... | 12-8 |
| Angle of Rotation Detector..... | 12-8 |
| Hall-Effect Compass..... | 12-8 |
| Security Door Ajar Alarm..... | 12-9 |
| Multiple Position Control System..... | 12-9 |
| Door Open Alarm..... | 12-10 |
| Appendix..... | A-1 |