

DIODES

681

|  | <i>page</i> |
|--|-------------|
| <b>Selection guide</b>   |             |
| Small-signal diodes . . . . .  | 1           |
| Tuner diodes . . . . .   | 2           |
| FM detection diode . . . . .   | 3           |
| Low-leakage diodes . . . . .   | 3           |
| Schottky barrier diodes . . . . .  | 3           |
| Voltage reference diodes . . . . .   | 3           |
| Stabistors . . . . .   | 4           |
| Voltage regulators . . . . .   | 4           |
| Transient suppressor diodes . . . . .  | 5           |
| Rectifiers . . . . .   | 5           |
| High-voltage tripler units . . . . .   | 8           |
| <b>Type number survey (alpha-numerical) . . . . .</b>                                | <b>9</b>    |
| <b>General information</b>   |             |
| Type designation . . . . .   | 11          |
| Rating system . . . . .  | 13          |
| Letter symbols . . . . .   | 15          |
| Quality conformance and reliability . . . . .  | 19          |
| General explanatory notes on rectifiers . . . . .                                    | 20          |
| Colour codes . . . . .   | 23          |
| Packing of SOD-80, SOT-23 and SOT-143 envelopes . . . . .                            | 25          |
| Packing of axial-leaded diodes . . . . .   | 29          |
| Packing of radial-leaded diodes . . . . .  | 32          |
| Mounting and soldering of axial-leaded diodes . . . . .                              | 34          |
| Soldering recommendations for SOT-23, SOT-89, SOT-143 and SOD-80 envelopes . . . . . | 37          |
| Thermal characteristics of SOT-23 and SOT-143 envelopes . . . . .                    | 43          |
| Thermal model for SOD-57, SOD-64, SOD-81 and SOD-84 envelopes . . . . .              | 47          |
| Custom-made E.H.T. stacks . . . . .  | 49          |
| <b>Device data in alpha-numerical sequence . . . . .</b>                             | <b>53</b>   |
| <b>Accessories . . . . .</b>   | <b>687</b>  |
| <b>Index of all devices in semiconductor Data Handbooks . . . . .</b>                | <b>689</b>  |